

ONTEC S C1 60 NM AT W TM-OS.C1ATN660W

Click on the selected icon to download the file:



No: 1025



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030




No: 1025



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1025




No: DIT_001




No: V3.0







Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	282 lm
Light source	LED
Maximum light power	2.5 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



					
2,5		8	18	-	-
3		8,5	20,5	-	-
4		9,5	25	-	-
5		9	27,5	-	-
6		6,5	28	-	-
7		5	26	-	-
8		4,5	23	-	-
9		4	20	-	-
10		4	15	-	-

E_{min} ≥ 1 lx