

ONTEC S M1 60 M AT B TM-OS.M1ATM660B

Click on the selected icon to download the file:



No: 1025



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030




No: 1025



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1025




No: DIT_001






No: V3.0



Producer	TM Technologie
Application	anti-panic lighting
Family	ONTEC S
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	360 lm
Light source	LED
Maximum light power	2.5 W
Active power	3.3 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm





2,5	3,5	10,5	3,5	10,5
3	4	11,5	4	11,5
4	5	13	5	13
5	4,5	15	4,5	15
6	4,5	16,5	4,5	16,5
7	4,5	17,5	4,5	17,5
8	4,5	18,5	4,5	18,5
9	5	19	5	19
10	4,5	20	4,5	20

$E_{min} \geq 0,5 \text{ lx}$