




# TM.ONTEC S20 M1X 60/180 M/NM AT

TM-S2.MXATX060W



## PARAMETERS

Application	anti-panic lighting
IP	IP65/IK08
IK	IK08
Version	AT - auto-test / self-test
Power supply	210÷250 V AC 50+60 Hz
Power supply CB	186÷254 V DC
Temperature range	5-40 °C
Material	PC
Colour	RAL9003
Duration time	1 h
Operating mode	M
Active power	3.8 W
Insulation class	2
Luminous flux	371 (1h); 154 (3h) lm
Battery	LiFePO4/C 3.2V 1.5Ah
Dimming mode	no



## PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	3,5 - 1h   3,0 - 3h	8,0 - 1h   7,0 - 3h
3,0	3,5 - 1h   3,5 - 3h	9,5 - 1h   8,0 - 3h
4,0	4,5 - 1h   4,0 - 3h	11,5 - 1h   9,5 - 3h
5,0	5,0 - 1h   4,0 - 3h	13,0 - 1h   11,0 - 3h
6,0	5,0 - 1h   3,5 - 3h	15,0 - 1h   12,5 - 3h
7,0	5,0 - 1h   3,5 - 3h	16,5 - 1h   13,5 - 3h
8,0	5,5 - 1h   3,5 - 3h	18,0 - 1h   14,0 - 3h
9,0	5,5 - 1h   3,0 - 3h	19,0 - 1h   14,5 - 3h
10,0	5,5 - 1h   2,0 - 3h	20,0 - 1h   15,0 - 3h

